

Model 1510

Single Point Load Cells

NEW!

Features

- ◆ Capacities: 100, 250, 500 kg
- ◆ Stainless Steel Construction
- ◆ Single Point 600x600mm Platform
- ◆ 6 wire (sense) circuit
- ◆ Fully welded, providing IP68 Protection
- ◆ OIML R60 approved
- ◆ Hazardous area approved to Eex ia IIC T6



Model 1510 is a high accuracy single point load cell ideally suited to industrial applications which undergo regular wash down, typically platforms, wall scales and other process weighing application in the food industry.

Hermetically sealed against moisture, the all welded construction of the model 1510 in combination with a polyurethane dual shielded cable, enables continuous operation in harsh environments whilst maintaining a high operating specification.

The two additional sense wires feed back the voltage reaching the load cell. Complete compensation of changes in lead resistance due to temperature change and/or cable extension, is achieved by feeding this voltage into the appropriate electronics.

TEDEA **th**
HUNTLEIGH
EXCELLENCE IN LOAD CELLS

INTERTECHNOLOGY
INC.

1 Scarsdale Road, Don Mills, ON M3B 2R2
Tel: 416-445-5500, Fax: 416-445-1170
Toll Free: 1-800-465-1600
E-Mail: sales@intertechnology.ca

Model 1510

Single Point Load Cells

Grade	E	C3**	Units
Rated Capacities	100, 250, 500		kg
Rated Output	2.0 ± 10%		mV/V
Total Error*	0.03	0.02	±% of Applied Load
Zero return after 30 mins	0.05	0.017	±% of Applied Load
Temperature Effect: On Output	0.003	0.0011	+-% of Applied Load/°C Rated
Temperature Effect: On Zero	0.01	0.0023	Output/°C
Eccentric Loading	0.005	0.0016	±% of Applied Load/cm
Zero Balance	10		±% of Rated Output
Temperature Range: Operating	-30 to +80		°C
Temperature Range: Compensated	-10 to +40		°C
Safe Overload	150		% of Rated Capacity
Ultimate Overload	200		% of Rated Capacity
Excitation: Recommended	10		Volts AC or DC
Excitation: Maximum	15		Volts AC or DC
Input Impedance	380±10		Ohms
Output Impedance	350±3		Ohms
Insulation Impedance	>1000		Mega Ohms
Deflection at Rated Capacity	<0.4		mm
Weight: (including cable)	2.4		kg
Construction	Stainless Steel		
Environmental Protection	IP68		
Cable	3 Meter (Standard), 6 Wire, Polyurethane Jacket, Dual Floating Screen		

*Total Error—According to OIML R60 **Standard utilization 50%, alternative utilization options down to %25 C4 Grade Available

Outline Dimensions All Capacities (in inches)

